

ConTEXt

title : ConTEXt User Module
subtitle : Fullpage documents
author : Wolfgang Schuster
date : April 22, 2010

Documentation

This module tries to copy the behaviour of the `fullpage` package for L^AT_EX, Mohamed Bana asked on the ConTeXt mailing list if a module with the same functions is available and this module was the result.

To use this module load it with the `\usemodule` command and pass a option with the `style` key in the optional argument.

```
\usemodule[fullpage][style={cm,empty}]
```

```
\starttext  
\input knuth  
\stoptext
```

The module provides the following styles:

in	set the margins to 1in
cm	set the margins to 1.5cm
plain	no header and narrow footer with 0.5cm
headings	narrow header and footer with 0.5cm
empty	no header and footer

Implementation

```
1 \unprotect
2 \startinterface all
  \setinterfacevariable {fullpage} {fullpage}
  \setinterfacevariable {in} {in}
  \setinterfacevariable {cm} {cm}
  \setinterfacevariable {plain} {plain}
  \setinterfacevariable {headings} {headings}
\stopinterface
3 \startmodule[\v!fullpage]
4 \setupmodule
  [\c!style={\v!in,\v!plain}]
5 \startsetups[\v!fullpage:\v!in]
6 \setuplayout
  [\c!backspace=1in,
   \c!width=\v!middle,
   \c!topspace=1in,
   \c!height=\v!middle]
7 \stopsetups
8 \startsetups[\v!fullpage:\v!cm]
9 \setuplayout
  [\c!backspace=15mm,
   \c!width=\v!middle,
   \c!topspace=15mm,
   \c!height=\v!middle]
10 \stopsetups
11 \startsetups[\v!fullpage:\v!plain]
12 \setuplayout
  [\c!header=0pt,
   \c!footer=.5in]
13 \stopsetups
14 \startsetups[\v!fullpage:\v!empty]
15 \setuplayout
  [\c!header=0pt,
   \c!footer=0pt]
```

```
16  \stopsetups  
17  \startsetups[\v!fullpage:\v!headings]  
18  \setuplayout  
    [\c!header=.5in,  
     \c!footer=.5in]  
19  \stopsetups  
20  \def\dofullpagelayout#1%  
    {\directsetup{\v!fullpage:#1}}  
21  \processcommacommand[\currentmoduleparameter\c!style]\dofullpagelayout  
22  \stopmodule  
23  \protect \endinput
```