

**NAME**

**t1mac** – translate a PFA or PFB PostScript Type 1 font into Macintosh format

**SYNOPSIS**

**t1mac** [--**macbinary** | --**applesingle** | --**appledouble** | --**binhex** | --**raw**] [--**filename** *name*] [*input* [*output*]]

**DESCRIPTION**

**t1mac** reads a PFA (hexadecimal) or PFB (binary) PostScript Type 1 font file and generates an equivalent Macintosh Type 1 font file. The output file can be in MacBinary II, AppleSingle, AppleDouble, or BinHex format, or it can be a raw resource fork. The default is MacBinary II; use an option to choose a different format. If the *output* file is not specified output goes to the standard output.

WARNING: The output of **t1mac** is not sufficient to use the font, since Macintoshes can't read raw Type 1 fonts. You will need to create a font suitcase containing bitmap fonts if you do not have such a suitcase for the font already. **t1mac** cannot help you do this.

**OPTIONS**

--**raw**, -**r**

Indicates that output should be a raw resource fork.

--**macbinary**

Indicates that output should be in MacBinary I or II format. This is the default.

--**applesingle**

Indicates that output should be in AppleSingle format.

--**appledouble**

Indicates that output should be in AppleDouble format.

--**binhex**

Indicates that output should be in BinHex 4.0 format.

--**filename**=*name*, -**n** *name*

Sets the Macintosh filename of the output font to *name*. The default is to construct the filename from the font's name using established Macintosh conventions. This option is not useful when output is a raw resource fork.

**SEE ALSO**

**t1unmac**(1), **t1ascii**(1), **t1binary**(1), **t1asm**(1), **t1disasm**(1)

**AUTHORS**

Eddie Kohler (ekohler@gmail.com)